

# NESS CCTV - FOR CONSISTENT COMMITMENT TO VALUE



100-367, 100-370



100-371



100-311



100-314 Optional ceiling suspension bracket.  
COMPATIBLE WITH ALL PRO SERIES HOUSINGS.  
Ceiling bracket and housing sold separately.



100-313 Optional Pole Mounting Bracket.  
COMPATIBLE WITH ALL PRO SERIES HOUSINGS.

## NESS PRO SERIES HOUSINGS

### WEATHERPROOF PROFESSIONAL CAMERA HOUSINGS

Ness Pro Series housings are the ultimate high quality outdoor camera enclosures at an affordable price. All models are supplied complete with swivel bracket, grommet cable entry, prefitted internal terminal strips and fuse.

**Model 100-367** has a cover which completely removes for total access to the camera. IP66 weatherproof rated, (dust tight, proof against powerful water jets).

**Model 100-370** as above and also has a built-in heater/window demister for cold climates. IP66 weatherproof rated.

**Model 100-371** has a rear hinged cover with hold-open latch. Features concealed cable entry and built-in heater/demister and cooling fan. IP44 weatherproof rated (Splash proof - Rain proof).

**Model 100-311** side opening design allows the lid to fully swing open while remaining attached to the body. Cable entry is fully concealed and secure via the bracket supplied. IP67 weatherproof rated (dust tight, waterproof). Also features a removable full length sun hood.

### POSSIBLY THE BEST ENVIRONMENTAL HOUSINGS MONEY CAN BUY! MOUNTING BRACKET INCLUDED.

100-367	PRO HOUSING inc wall bracket
100-370	PRO HOUSING WITH HEATER inc wall bracket
100-371	PRO HOUSING WITH HEATER/FAN inc wall bracket
100-311	PRO HOUSING SIDE OPENING inc wall bracket
100-313	POLE MOUNTING BRACKET suits all models
100-314	CEILING SUSPENSION BRACKET suits all models

Specifications	100-367	100-370	100-371	100-311
WEATHER PROTECTION	IP66		IP44	IP67
HEATER	no	yes	yes	no
COOLING	no	no	yes	no
INTERNAL DIMENSIONS (W x H x L) camera capacity	90 x 70 x 230 mm		105 x 80 x 300 mm	90 x 70 x 230 mm
EXTERNAL DIMENSIONS (W x H x L) Body only	127 x 124 x 390 mm		135 x 158 x 450 mm	140 x 120 x 380 mm
INTERNAL ACCESS	Fully removable lid		Rear hinge	Side hinge
OPERATING VOLTAGE	-	24V AC for heater	24V AC for heater/fan	-
CURRENT DRAW	-	2A	2A	-
WEIGHT inc bracket	2.5kg	2.6kg	3.65kg	3.1kg

SYDNEY 02 8825 9222  
sales@ness.com.au

MELBOURNE 03 9875 6400  
nessmelb@ness.com.au

BRISBANE 07 3399 4910  
nessbris@ness.com.au

PERTH 08 9328 2511  
nessper@ness.com.au

ADELAIDE 08 8277 7255  
adelaide@ness.com.au



**CCTV Products**

www.ness.com.au

